

# Specifications

Run

by Abbott Miller

300226

## Application

Walls

## Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: Protective Topcoat

Backing: Cotton

Width: 52" (132cm)

Repeat: 23 1/4" V, 52" H

(59cm V, 132cm H)

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](http://maharam.com).

## Price

\$42.50 / C\$64.25 (FOB destination) / C\$60.75 (FOB origin)

## Maintenance

W-Clean with water-based cleanser.

## Testing

Flammability: ASTM E84 Adhered

CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications  
Run  
by Abbott Miller  
300226

**Environmental**  
Greenguard Certified  
Free of Intentionally Added PFAS

**Warranty**  
10 years.

© 2011 Knoll, Inc.

Complete product information at [knolltextiles.com](http://knolltextiles.com)  
800.645.3943




001 Coral



002 Leaf



003 Branch



005 Water