

399426 Sari maharam

# **Application**

Walls

## **Characteristics**

Content: 100% Non-Phthalate Vinyl

Finish: None

Backing: Polyester/Cotton Osnaburg

Width: 54" (137cm) Repeat: Non-match Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

### Price

\$35.00 / C\$53.50 (FOB destination) C\$50.00 (FOB origin)

## **Testing**

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered BS 476 Adhered\*

CAN ULC S102 Adhered

EN 13501 Adhered GB 8624 Adhered\* ISO 5660 Adhered

\*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours



#### Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.



#### **Environmental**

FR Free

Free of Intentionally Added PFAS

Non-Phthalate Vinyl

# Warranty

10 years. See Terms and Conditions for more information.

© 2009 Maharam

Last updated June 19, 2025