



Design

Teresita Fernández

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' H x 36' 8" W (305cm x

1118cm)

Traffic: Moderate Traffic Customs: Repeatable Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis.

Maintenance

W-Clean with water-based cleanser.

Testing

Flammability: AS/NZS 3837 Adhered ASTM E84 Adhered CAN ULC S102 Adhered ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Environmental

Greenguard Gold Certified LBC Red List Free Contains Bio-Based Content FR Free

Free of Intentionally Added PFAS

Brief

Teresita Fernández composed Sfumato from thousands of individual graphite fragments embedded into the wall and smudged to create marks suggestive of cosmic trails. In the macro view, the piece functions as a constellation while further inspection reveals the intricate surface detail of each element.

Warranty

3 years. See Terms and Conditions for more information.

© 2016 Teresita Fern ndez, Maharam under license

Last updated May 1, 2025