

Specifications

Simple

300153

Application

Walls

Characteristics

Content: 100% Vinyl

Finish: PFAS-Free Protective Topcoat

Backing: Polyester/Cotton Osnaburg

Width: 50" (127cm)

Bolt Size: 33 yards (30 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: Great Britain

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$27.00 / C\$42.25 (FOB destination) / C\$38.75 (FOB origin)

Maintenance

W-Clean with water-based cleanser.

Testing

Flammability: ASTM E84 Adhered

CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 200+ hours



Specifications
Simple
300153

Environmental
Free of Intentionally Added PFAS

Warranty
10 years.

© 2019 Knoll, Inc.

Complete product information at knolltextiles.com
800.645.3943




001 Icicle




002 Canvas




003 Harbor



004 Firelight



005 Armadillo



006 Bronze



007 Riverbed



008 Frolic



009 Polished



010 Stratosphere



011 Tin



012 Shadow Box