Specifications Sinter 300038

Application

Walls

Characteristics

Content: 70% Cellulose, 30% Polyester Finish: PFAS-Free Water Repellent Backing: Cellulose / Polyester Width: 54" (137cm) Bolt Size: 55 yards (50 m) Weight: 9.7 oz/ly (300 gr/lm) Traffic: Moderate Traffic Country of Origin: Netherlands Note: This product uses iridescent inks which produce subtle variations in color when viewed from different angles and under different light sources. Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$44.50/

Maintenance

X-Vacuum or brush lightly to remove surface dust. ☆ ☆ ⊠ ⋧ ∞

Testing

Flammability: ASTM E84 Adhered EN 13501 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications Sinter 300038

Environmental

Greenguard Gold Certified Healthier Hospitals Compliant LBC Red List Free **REACH** Compliant Contains Bio-Based Content Contains Forest Stewardship Council (Fsc) Certified Content FR Free Free of Intentionally Added PFAS

Warranty

1 year.

© 2019 Maharam

Complete product information at maharam.com 800.645.3943

009 Vicuna













001 Retrograde

002 Masa





008 Orbital

010 Tiramisu