

001 Blizzard

**Application**

Walls

**Characteristics**

Content: 100% Non-Phthalate Vinyl  
Finish: PFAS-Free Protective Topcoat  
Backing: Polyester/Cotton Osnaburg  
Width: 54" (137cm)  
Repeat: Non-match  
Bolt Size: 30 yards (27 m)  
Class: Type II  
Weight: 20 oz/ly (600 gr/lm)  
Traffic: High Traffic  
Country of Origin: USA  
Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.  
Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

**Price**


\$30.00 / C\$46.50 (FOB destination)  
C\$43.00 (FOB origin)

**Testing**

Flammability: AS/NZS 3837 Adhered  
ASTM E84 Adhered  
BS 476 Adhered\*  
CAN ULC S102 Adhered  
EN 13501 Adhered\*  
GB 8624 Adhered\*  
ISO 5660 Adhered  
\*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours  


**Maintenance**

W/B-Clean with water-based cleanser or diluted household bleach.  


**Environmental**

FR Free  
Free of Intentionally Added PFAS  
Non-Phthalate Vinyl

**Warranty**

10 years. See Terms and Conditions for more information.

© 2012 Maharam

Last updated August 2, 2025