

Specifications

Sullivan

300213

Knoll Textiles

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: None

Backing: Polyester/Cotton Osnaburg

Width: 52" (132cm)

Repeat: 26 1/2" V, 54" H

(67cm V, 137cm H)

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$42.50 / C\$65.25 (FOB destination) / C\$60.75 (FOB origin)

Maintenance

W-Clean with water-based cleanser.

Testing

Flammability: ASTM E84 Adhered

CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications
Sullivan
300213

Environmental
Greenguard Certified
Free of Intentionally Added PFAS
Non-Phthalate Vinyl

Warranty
10 years.

© 2013 Knoll, Inc.


Complete product information at knolltextiles.com
800.645.3943




001 Windmill



002 Comet



003 Spice




004 Burst



005 Flute



006 Foil



007 Platinum



008 Alloy



009 Inkwell