

Specifications

Sunny

by Alex Katz

399947

maharam

Application

Walls

Characteristics

Content: 83% Cellulose, 17% Polyester

Finish: PFAS-Free Protective Topcoat

Backing: None

Width: 27" (69cm)

Repeat: 20 1/2" V, 27" H

(52cm V, 69cm H)

Weight: 4.8 oz/ly (100 gr/lm)

Traffic: Moderate Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$215.00 / C\$310.75 (FOB destination) / C\$307.25 (FOB origin)

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications

Sunny

by Alex Katz

399947

Environmental

Greenguard Gold Certified

Healthier Hospitals Compliant

LBC Red List Free

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

Warranty

3 years.

© 2016 Alex Katz, Maharam under license

Complete product information at maharam.com

800.645.3943



001