

Specifications

System

399600

maharam

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: Protective Topcoat

Backing: Polyester / Cellulose

Width: 52" (132cm)

Repeat: 22 1/4" V, 26" H

(57cm V, 66cm H)

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$40.00 / C\$60.75 (FOB destination) / C\$57.25 (FOB origin)

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

CAN ULC S102 Adhered

EN 13501 Adhered*

GB 8624 Adhered*

ISO 5660 Adhered

*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours



Specifications
System
399600

maharam

Environmental

FR Free
Free of Intentionally Added PFAS
Non-Phthalate Vinyl

Warranty

10 years.

© 2013 Maharam

Complete product information at maharam.com
800.645.3943



001 Black




002 Gold



003 Stone



004 Tomato




010 Cobalt




011 Capri




012 Haze



013 Dynamic



015 Quarry



016 Slate