

Specifications

maharam

Taut

399568

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: PFAS-Free Protective Topcoat

Backing: Polyester/Cotton Osnaburg

Width: 54" (137cm)

Repeat: Non-match

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note: This product uses iridescent inks which produce subtle variations in color when viewed from different angles and under different light sources.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$34.00 / C\$52.25 (FOB destination) / C\$48.75 (FOB origin)

Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.



Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

BS 476 Adhered*

CAN ULC S102 Adhered

EN 13501 Adhered*

GB 8624 Adhered*

ISO 5660 Adhered

*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours



Specifications

Taut

399568

maharam

Environmental

FR Free
Free of Intentionally Added PFAS
Non-Phthalate Vinyl

Warranty

10 years.

© 2012 Maharam

Complete product information at maharam.com
800.645.3943



001 Aura



002 Whir




003 Vanish



004 Mood



005 Diadem



008 Wax



010 Splendor



012 Renew




013 Tonic



014 Horizon



015 Ice



016 Reflect



018 Sentry



019 Majesty