

Specifications  
Tek-Wall 1003  
300089

**maharam**

**Application**

Upholstered Walls, Walls

**Characteristics**

Content: 62% Solution-Dyed Polyolefin, 38% Polyester

Finish: PFAS-Free Water Repellent

Backing: Acrylic

Width: 56" (142cm)

Bolt Size: 40 yards (37 m)

Weight: 17.5 oz/ly (500 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment.

**Price**

\$34.50 / C\$53.00 (FOB destination) / C\$49.50 (FOB origin)

**Maintenance**

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.



**Testing**

Acoustics: ASTM C423, 0.75 NRC

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

ASTM E84 Unadhered

CAN ULC S102 Adhered

CAN ULC S102 Unadhered

EN 13501 Adhered\*

EN 13501 Unadhered\*

GB 8624 Adhered\*

GB 8624 Unadhered\*

ISO 5660 Adhered

\*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours



Specifications  
Tek-Wall 1003  
300089

**Environmental**

Greenguard Gold Certified  
LBC Red List Free  
REACH Compliant  
FR Free  
Free of Intentionally Added PFAS

**Warranty**

10 years: Walls  
3 years: Upholstered Walls.

© 2022 Maharam

Complete product information at [maharam.com](http://maharam.com)  
800.645.3943

