Specifications Tek-Wall Bastion 300090

Application

Upholstered Walls, Walls

Characteristics

Content: 55% Polyester, 45% Solution-Dyed Polyolefin Finish: Stain Repellent Backing: Acrylic Width: 56" (142cm) Bolt Size: 40 yards (37 m) Weight: 15.3 oz/ly (500 gr/lm) Traffic: High Traffic Country of Origin: USA Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$33.50 / C\$51.50 (FOB destination) / C\$48.00 (FOB origin)

Maintenance

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach. ☆ △ ⊠ ☆ ⊗

Testing

Acoustics: ASTM C423, 0.80 NRC

Flammability: ASTM E84 Adhered ASTM E84 Unadhered CAN ULC S102 Adhered CAN ULC S102 Unadhered EN 13501 Adhered* EN 13501 Unadhered* GB 8624 Adhered* *passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours **★** *●* ★

Specifications Tek-Wall Bastion 300090

Environmental

Greenguard Gold Certified REACH Compliant FR Free

Warranty

10 years: Walls 3 years: Upholstered Walls.

© 2022 Maharam

Complete product information at maharam.com 800.645.3943

