

Application

Upholstered Walls, Walls

Characteristics

Content: 55% Polyester, 45% Solution-Dyed Polyolefin

Finish: Stain Repellent

Backing: Acrylic Width: 56" (142cm)

Bolt Size: 40 yards (37 m) Weight: 15.3 oz/ly (500 gr/lm)

Traffic: High Traffic Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$33.50 / C\$52.50 (FOB destination) C\$48.00 (FOB origin)

Testing

Acoustics: ASTM C423, 0.80 NRC

Flammability: ASTM E84 Adhered

ASTM E84 Unadhered
CAN ULC S102 Adhered
CAN ULC S102 Unadhered

EN 13501 Adhered* EN 13501 Unadhered* GB 8624 Adhered*

*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours



Maintenance

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

Environmental

Greenguard Gold Certified REACH Compliant FR Free

Warranty

10 years: Walls3 years: Upholstered Walls.See Terms and Conditions for more information.

© 2022 Maharam

Last updated May 1, 2025