

Specifications
Tek-Wall Fleet
300113

maharam

Application

Upholstered Walls, Walls

Characteristics

Content: 60% Polyester, 40% Solution-Dyed Polyolefin

Finish: None

Backing: Acrylic

Width: 56" (142cm)

Bolt Size: 60 yards (55 m)

Weight: 15.7 oz/ly (500 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$30.50 / C\$47.25 (FOB destination) / C\$43.75 (FOB origin)

Maintenance

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

☒ △ ☒ ☒ Ⓜ

Testing

Acoustics: ASTM C423, 0.85 NRC

Flammability: ASTM E84 Adhered

ASTM E84 Unadhered*

CAN ULC S102 Adhered

CAN ULC S102 Unadhered

EN 13501 Adhered*

EN 13501 Unadhered*

GB 8624 Adhered*

*passes with additional treatment

Lightfastness: AATCC 16.3, 100+ hours

☀ 🔥 💧 ☆

Specifications
Tek-Wall Fleet
300113

maharam

Environmental

Greenguard Gold Certified
REACH Compliant
FR Free
Free of Intentionally Added PFAS

Warranty

10 years: Walls
3 years: Upholstered Walls.

© 2023 Maharam

Complete product information at maharam.com
800.645.3943



001 Reach



002 Latitude



003 Boreal



004 Standstill



005 Vision



006 Stroll



007 Replica