

Specifications

Tek-Wall Lucent

300066

maharam

Application

Upholstered Walls, Walls

Characteristics

Content: 60% Polyester, 40% Post-Consumer Recycled Polyester

Finish: Stain Repellent

Backing: Acrylic

Width: 57" (145cm)

Bolt Size: 30 yards (27 m)

Weight: 16.7 oz/ly (500 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$40.00 / C\$60.75 (FOB destination) / C\$57.25 (FOB origin)

Maintenance

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.



Testing

Acoustics: ASTM C423, 0.85 NRC

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

ASTM E84 Unadhered

BS 476 Adhered*

BS 476 Unadhered*

CAN ULC S102 Adhered

CAN ULC S102 Unadhered

EN 13501 Adhered*

EN 13501 Unadhered*

GB 8624 Adhered*

ISO 5660 Adhered

*passes with additional treatment

Lightfastness: AATCC 16.3, 100+ hours



Specifications
Tek-Wall Lucent
300066

maharam

Environmental

Greenguard Gold Certified
REACH Compliant
Contains Recycled Content
FR Free

Warranty

10 years: Walls
3 years: Upholstered Walls.

© 2020 Maharam

Complete product information at maharam.com
800.645.3943



001 Icefall



002 Village



003 Ammonite



004 Mythical



005 Darkness



006 Chalkboard



007 Riverway



008 Aventurine



010 Ecstatic




011 Arrowhead



012 Ironbark



013 Merriment



014 Sundress



015 Cloudberry