

Specifications

Tek-Wall Ridge

300048

maharam

Application

Upholstered Walls, Walls

Characteristics

Content: 93% Polyester, 5% Post-Consumer Recycled Polyester, 2% Post-Industrial Recycled Polyester

Finish: Stain Repellent

Backing: Acrylic

Width: 55" (140cm)

Bolt Size: 30 yards (27 m)

Weight: 26.3 oz/ly (800 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note: Variations in color and texture are inherent to this textile.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$37.00 / C\$57.50 (FOB destination) / C\$53.00 (FOB origin)

Maintenance

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.



Testing

Acoustics: ASTM C423, 0.50 NRC

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

ASTM E84 Unadhered

BS 476 Adhered*

BS 476 Unadhered*

CAN ULC S102 Adhered

CAN ULC S102 Unadhered

EN 13501 Adhered*

EN 13501 Unadhered*

GB 8624 Adhered*

ISO 5660 Adhered

*passes with additional treatment

Lightfastness: AATCC 16.3, 80+ hours



Specifications
Tek-Wall Ridge
300048

maharam

Environmental


Greenguard Gold Certified
REACH Compliant
Contains Recycled Content

Warranty

10 years: Walls
3 years: Upholstered Walls.

© 2019 Maharam

Complete product information at maharam.com
800.645.3943




001 Snowman



002 Tonic




003 Siesta




004 Wombat



005 Drama




006 Gladiator



008 Splash



009 Sojourn



010 Sprinkler



011 Arroyo



013 Wasp




014 Quicksand




015 Savor



016 Amity



017 Lox



018 Eruption



019 Hula