

Application

Upholstered Walls, Walls

Characteristics

Content: 93% Polyester, 5% Post-Consumer Recycled Polyester, 2% Post-Industrial Recycled Polyester

Finish: Stain Repellent Backing: Acrylic

Width: 55" (140cm)
Bolt Size: 30 yards (27 m)
Weight: 26.3 oz/ly (800 gr/lm)

Traffic: High Traffic
Country of Origin: USA

Note: Variations in color and texture are inherent to

this textile.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$37.00 / C\$56.50 (FOB destination) C\$53.00 (FOB origin)

Testing

Acoustics: ASTM C423, 0.50 NRC

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered
ASTM E84 Unadhered
BS 476 Adhered*
BS 476 Unadhered*
CAN ULC S102 Adhered
CAN ULC S102 Unadhered
EN 13501 Adhered*
EN 13501 Unadhered*
GB 8624 Adhered*
ISO 5660 Adhered

*passes with additional treatment

Lightfastness: AATCC 16.3, 80+ hours



Maintenance

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

Environmental

Greenguard Gold Certified REACH Compliant Contains Recycled Content

Warranty

10 years: Walls

3 years: Upholstered Walls.

See Terms and Conditions for more information.

© 2019 Maharam

Last updated August 2, 2025