

Specifications
Tek-Wall Strake
300076

maharam

Application

Upholstered Walls, Walls

Characteristics

Content: 100% Polyester

Finish: None

Backing: Acrylic

Width: 55" (140cm)

Bolt Size: 60 yards (55 m)

Weight: 13.2 oz/ly (400 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$37.00 / C\$57.50 (FOB destination) / C\$53.00 (FOB origin)

Maintenance

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.



Testing

Acoustics: ASTM C423, 0.65 NRC

Flammability: AS/NZS 3837 Unadhered

ASTM E84 Adhered

ASTM E84 Unadhered

CAN ULC S102 Adhered

CAN ULC S102 Unadhered

EN 13501 Adhered*

EN 13501 Unadhered*

GB 8624 Adhered*

ISO 5660 Unadhered

*passes with additional treatment

Lightfastness: AATCC 16.3, 100+ hours



Specifications
Tek-Wall Strake
300076

Environmental

Greenguard Gold Certified
REACH Compliant
FR Free
Free of Intentionally Added PFAS

Warranty

10 years: Walls
3 years: Upholstered Walls.

© 2021 Maharam

Complete product information at maharam.com
800.645.3943



001 Baroque



002 Memory



003 Statue



004 Riverbed



005 Turntable



006 Wetlands



007 Raku



008 Colosseum



009 Fragment



010 Banjo



011 Nocturne