

Application

Upholstered Walls, Walls

Characteristics

Content: 100% Polyester

Finish: None Backing: Acrylic Width: 55" (140cm)

Bolt Size: 60 yards (55 m) Weight: 13.2 oz/ly (400 gr/lm)

Traffic: High Traffic Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$37.00 / C\$56.50 (FOB destination) C\$53.00 (FOB origin)

Testing

Acoustics: ASTM C423, 0.65 NRC

Flammability: AS/NZS 3837 Unadhered

ASTM E84 Adhered ASTM E84 Unadhered CAN ULC S102 Adhered CAN ULC S102 Unadhered

EN 13501 Adhered* EN 13501 Unadhered* GB 8624 Adhered* ISO 5660 Unadhered

*passes with additional treatment

Lightfastness: AATCC 16.3, 100+ hours



Maintenance

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

Environmental

Greenguard Gold Certified
REACH Compliant
FR Free
Free of Intention alls Added

Free of Intentionally Added PFAS

Warranty

10 years: Walls

3 years: Upholstered Walls.

See Terms and Conditions for more information.

© 2021 Maharam

Last updated June 16, 2025