

Application

Upholstered Walls, Walls

Characteristics

Content: 100% Polyester

Finish: None Backing: Acrylic Width: 55" (140cm)

Bolt Size: 60 yards (55 m) Weight: 13.2 oz/ly (400 gr/lm)

Traffic: High Traffic Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation

Guidelines included in each shipment.

Price

\$37.00 / C\$56.50 (FOB destination) C\$53.00 (FOB origin)

Testing

Acoustics: ASTM C423, 0.65 NRC

Flammability: AS/NZS 3837 Unadhered

ASTM E84 Adhered ASTM E84 Unadhered CAN ULC S102 Adhered CAN ULC S102 Unadhered

EN 13501 Adhered* EN 13501 Unadhered* GB 8624 Adhered* ISO 5660 Unadhered

*passes with additional treatment

Lightfastness: AATCC 16.3, 100+ hours



Maintenance

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

Environmental

Greenguard Gold Certified REACH Compliant FR Free Free of Intentionally Added PFAS

Warranty

10 years: Walls3 years: Upholstered Walls.See Terms and Conditions for more information.

© 2021 Maharam

Last updated August 31, 2025