

# Specifications

## The Future Is Always Bright

### 399507

**maharam**

#### Application

Walls

#### Characteristics

Content: 65% Cellulose, 35% Latex

Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' H x 27' 10" W (305cm x 848cm)

Traffic: Moderate Traffic

Customs: Scalable

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](https://maharam.com).

#### Price

Installation is sized, priced and produced on a project-specific basis.

#### Maintenance

W-Clean with water-based cleanser.



#### Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

CAN ULC S102 Adhered

ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications  
The Future Is Always Bright  
399507

**maharam**

**Environmental**

Greenguard Gold Certified  
LBC Red List Free  
Contains Bio-Based Content  
FR Free  
Free of Intentionally Added PFAS

**Warranty**

3 years.

**Disclaimer**

This artwork contains language or imagery that may not be suitable for all audiences.

© 2010 Tomokazu Matsuyama, Maharam under license

Complete product information at [maharam.com](http://maharam.com)  
800.645.3943



001