Specifications **maharam**Titan

300123

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl Finish: PFAS-Free Protective Topcoat Backing: Polyester/Cotton Osnaburg

Width: 54" (137cm) Repeat: Non-match Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic Country of Origin: USA

Note: This product uses iridescent inks which produce subtle variations in color when viewed from different angles and under different light sources.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$33.00 / C\$50.75 (FOB destination) / C\$47.25 (FOB origin)

Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.



Testing

Flammability: ASTM E84 Adhered CAN ULC S102 Adhered EN 13501 Adhered GB 8624 Adhered*

*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours



Specifications **maharam** Titan

300123

Environmental

Greenguard Certified FR Free Free of Intentionally Added PFAS Non-Phthalate Vinyl Made In USA

Warranty

10 years.

© 2024 Maharam

Complete product information at maharam.com 800.645.3943

Specifications maharam

Titan 300123

