



Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl
Finish: PFAS-Free Protective Topcoat
Backing: Polyester/Cotton Osnaburg
Width: 54" (137cm)
Repeat: Non-match
Bolt Size: 30 yards (27 m)
Class: Type II
Weight: 20 oz/ly (600 gr/lm)
Traffic: High Traffic
Country of Origin: USA
Note: This product uses iridescent inks which produce subtle variations in color when viewed from different angles and under different light sources.
Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.
Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$33.00 / C\$50.75 (FOB destination)
C\$47.25 (FOB origin)

Testing

Flammability: ASTM E84 Adhered
CAN ULC S102 Adhered
EN 13501 Adhered
GB 8624 Adhered*
*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours



Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.
☒ △ ☒ ☒ Ⓢ

Environmental

Greenguard Certified
FR Free
Free of Intentionally Added PFAS
Non-Phthalate Vinyl
Made In USA

Warranty

10 years. See Terms and Conditions for more information.

© 2024 Maharam

Last updated August 2, 2025