Specifications **maharam**

Trance 300033

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl Finish: PFAS-Free Protective Topcoat Backing: Polyester / Cellulose

Width: 52" (132cm) Repeat: Non-match Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$29.00 / C\$45.00 (FOB destination) / C\$41.50 (FOB origin)

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered ASTM E84 Adhered CAN ULC S102 Adhered EN 13501 Adhered* GB 8624 Adhered* ISO 5660 Adhered *passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours



Specifications maharam Trance

300033

Environmental

Greenguard Certified REACH Compliant FR Free Free of Intentionally Added PFAS Non-Phthalate Vinyl

Warranty

10 years.

© 2019 Maharam

Complete product information at maharam.com 800.645.3943













001 Nexus