

300054 Trim

maharam

Application

Walls

Characteristics Content: 100% Cellulose Finish: None Backing: 84% Polyester, 16% Post-Consumer Recycled Polyester Width: 52" (132cm) Repeat: 19 1/2" V, 26" H (50cm V, 66cm H) Bolt Size: 30 yards (27 m) Weight: 8.5 oz/ly (300 gr/lm) Traffic: Moderate Traffic Country of Origin: USA Note: This product is available in custom colors for a minimum of 30 yards. Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price \$65.00 / C\$96.50 (FOB destination) C\$93.00 (FOB origin)

Testing Flammability: AS/NZS 3837 Adhered ASTM E84 Adhered CAN ULC S102 Adhered EN 13501 Adhered* ISO 5660 Adhered *passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours

Maintenance W-Clean with water-based cleanser. ☆☆☆☆☆☆

Environmental Greenguard Gold Certified Healthier Hospitals Compliant LBC Red List Free Contains Bio-Based Content FR Free Free of Intentionally Added PFAS

Warranty 3 years. See Terms and Conditions for more information.

© 2019 Maharam

Last updated August 15, 2025

maharam