

# Specifications

**maharam**

Type

399538

## Application

Walls

## Characteristics

Content: 65% Cellulose, 35% Latex

Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' H x 15' W (305cm x 457cm)

Traffic: Moderate Traffic

Customs: Repeatable, Scalable

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

## Price

Installation is sized, priced and produced on a project-specific basis.

## Maintenance

W-Clean with water-based cleanser.

☒ ☒ ☒ ☒ ☒

## Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

CAN ULC S102 Adhered

ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours

☀ 🔥 🖨

## Specifications

Type

399538

**maharam**

### **Environmental**

Greenguard Gold Certified

LBC Red List Free

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

### **Warranty**

3 years.

© 2011 Polly Apfelbaum, Maharam under license

Complete product information at [maharam.com](http://maharam.com)

800.645.3943



001