Specifications Knoll Textiles
Ultrasuede

466701

Application

Seating, Systems, Upholstered Walls, Walls

Characteristics

Content: 80% Polyester, 20% Polyurethane

Finish: None
Backing: None
Width: 54" (137cm)
Bolt Size: 33 yards (30 m)
Weight: 17 oz/ly (500 gr/lm)
Country of Origin: Japan

Price

\$126.00 / C\$183.50 (FOB destination) / C\$180.00 (FOB origin)

Maintenance

W/S-Clean with water-based cleanser or mild, water-free dry cleaning solvent.

Testina

Abrasion: ASTM D4157, 200,000 double rubs Wyzenbeek

Note: Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

Multiple factors affect fabric durability and appearance retention.

Acoustics: ASTM C423, 0.70 NRC

Flammability: ASTM E84 Adhered ASTM E84 Unadhered

BS 5852 - PART 1*
BS 5852 Crib 5*
CAL 117-2013

CAN ULC S102 Adhered CAN ULC S102 Unadhered

EN 1021-1* EN 1021-2* NFPA 260

*passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours

1 * # 0 ×

Specifications Knoll Textiles
Ultrasuede

466701

Environmental
Greenguard Gold Certified
LBC Red List Free
FR Free
Free of Intentionally Added PFAS

Warranty

5 years.

© 2006 Knoll, Inc.

Complete product information at knolltextiles.com 800.645.3943

Knoll Textiles

Specifications Ultrasuede 466701



Knoll Textiles

Specifications Ultrasuede 466701

