




Application Seating, Upholstered Walls, Walls	Price \$126.00 / C\$183.50 (FOB destination) C\$180.00 (FOB origin)	Maintenance W/S-Clean with water-based cleanser or mild, water-free dry cleaning solvent.
Characteristics Content: 80% Polyester, 20% Polyurethane Finish: None Backing: None Width: 54" (137cm) Bolt Size: 33 yards (30 m) Weight: 17 oz/ly (500 gr/lm) Country of Origin: Japan	Testing Abrasion: ASTM D4157, 200,000 double rubs Wyzenbeek Note: Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention. Acoustics: ASTM C423, 0.70 NRC Flammability: ASTM E84 Adhered ASTM E84 Unadhered BS 5852 - PART 1* BS 5852 Crib 5* CAL 117-2013 CAN ULC S102 Adhered CAN ULC S102 Unadhered EN 1021-1* EN 1021-2* NFPA 260 *passes with additional treatment Lightfastness: AATCC 16.3, 40+ hours 	Environmental Greenguard Gold Certified LBC Red List Free FR Free Free of Intentionally Added PFAS Warranty 5 years. See Terms and Conditions for more information. © 2006 Knoll, Inc. Last updated August 21, 2025