

## Specifications

Ume

by Toyo Ito

399741

**maharam**

### Application

Walls

### Characteristics

Content: 83% Cellulose, 17% Polyester

Finish: PFAS-Free Protective Topcoat

Backing: None

Width: 27" (69cm)

Repeat: 27" V, 27" H

(69cm V, 69cm H)

Weight: 4.8 oz/ly (100 gr/lm)

Traffic: Moderate Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment.

### Price

\$215.00 / C\$310.75 (FOB destination) / C\$307.25 (FOB origin)

### Maintenance

W-Clean with water-based cleanser.



### Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



## Specifications

Ume

by Toyo Ito

399741

### **Environmental**

Greenguard Gold Certified

Healthier Hospitals Compliant

LBC Red List Free

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

### **Warranty**

3 years.

© 2015 Toyo Ito, Maharam under license

Complete product information at [maharam.com](http://maharam.com)

800.645.3943



001