





001

Design

Joost Grootens

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex
Finish: PFAS-Free Protective Topcoat
Backing: None
Reference Dimension: 10' H x 10' W (305cm x 305cm)
Traffic: Moderate Traffic
Customs: Scalable
Country of Origin: USA
Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.
Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis.

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered
ASTM E84 Adhered
CAN ULC S102 Adhered
ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours

Environmental

Greenguard Gold Certified
LBC Red List Free
Contains Bio-Based Content
FR Free
Free of Intentionally Added PFAS

Brief

The acronym "Vinex" refers to a supplement of the Dutch government's Fourth Report on Spatial Planning, which was published in the early 1990s and determined the policy direction for housing development in the Netherlands. The definitive reference work on the fifty-two Vinex districts, Vinex Atlas, designed by Studio Joost Grootens, is based on aerial views, plans, site data, and recent on-site photographs. Page 91 documents two districts in Apeldoorn, currently the Netherlands' twelfth-largest city.

Warranty

3 years. See Terms and Conditions for more information.

© 2012 Joost Grootens, Maharam under license

Last updated August 2, 2025