

Specifications

Vitrine

300050

maharam

Application

Walls

Characteristics

Content: 100% Cellulose

Finish: None

Backing: 84% Polyester, 16% Post-Consumer Recycled Polyester

Width: 52" (132cm)

Repeat: 19 3/4" V, 26" H

(50cm V, 66cm H)

Bolt Size: 30 yards (27 m)

Weight: 8.5 oz/ly (300 gr/lm)

Traffic: Moderate Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment.

Price

\$65.00 / C\$96.50 (FOB destination) / C\$93.00 (FOB origin)

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

CAN ULC S102 Adhered

EN 13501 Adhered*

ISO 5660 Adhered

*passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours



Specifications
Vitrine
300050

maharam

Environmental

Greenguard Gold Certified
Healthier Hospitals Compliant
LBC Red List Free
Contains Bio-Based Content
FR Free
Free of Intentionally Added PFAS

Warranty

3 years.

© 2019 Maharam

Complete product information at maharam.com
800.645.3943



001 Skywalk



002 Ivy



003 Zellige



004 Nightingale