Specifications **maharam**Vitrine

300050

Application

Walls

Characteristics

Content: 100% Cellulose

Finish: None

Backing: 84% Polyester, 16% Post-Consumer Recycled Polyester

Width: 52" (132cm) Repeat: 19 3/4" V, 26" H (50cm V, 66cm H) Bolt Size: 30 yards (27 m)

Weight: 8.5 oz/ly (300 gr/lm)
Traffic: Moderate Traffic
Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$65.00 / C\$96.50 (FOB destination) / C\$93.00 (FOB origin)

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered ASTM E84 Adhered CAN ULC S102 Adhered EN 13501 Adhered* ISO 5660 Adhered *passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours

* *

Specifications **maharam** Vitrine

300050

Environmental

Greenguard Gold Certified Healthier Hospitals Compliant LBC Red List Free Contains Bio-Based Content FR Free Free of Intentionally Added PFAS

Warranty

3 years.

© 2019 Maharam

Complete product information at maharam.com 800.645.3943









7.25