



001 Skywalk



002 Ivy



003 Zellige



004 Nightingale

Application

Walls

Characteristics

Content: 100% Cellulose
Finish: None
Backing: 84% Polyester, 16% Post-Consumer Recycled Polyester
Width: 52" (132cm)
Repeat: 19 3/4" V, 26" H
(50cm V, 66cm H)
Bolt Size: 30 yards (27 m)
Weight: 8.5 oz/ly (300 gr/lm)
Traffic: Moderate Traffic
Country of Origin: USA
Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.
Application must conform to current Installation Guidelines included in each shipment.

Price






\$65.00 / C\$96.50 (FOB destination)
C\$93.00 (FOB origin)

Testing

Flammability: AS/NZS 3837 Adhered
ASTM E84 Adhered
CAN ULC S102 Adhered
EN 13501 Adhered*
ISO 5660 Adhered
*passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours
 

Maintenance

W-Clean with water-based cleanser.
    

Environmental

Greenguard Gold Certified
Healthier Hospitals Compliant
LBC Red List Free
Contains Bio-Based Content
FR Free
Free of Intentionally Added PFAS

Warranty

3 years. See Terms and Conditions for more information.

© 2019 Maharam

Last updated September 1, 2025