

Specifications

Windswept

300245

Knoll Textiles

Application

Walls

Characteristics

Content: 76% Thermoplastic Olefin, 24% Post-Industrial Recycled Thermoplastic Olefin

Finish: None

Backing: Polyester/Cotton Osnaburg

Width: 52" (132cm)

Repeat: 18" V, 53" H

(46cm V, 135cm H)

Bolt Size: 30 yards (27 m)

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$37.50 / C\$57.25 (FOB destination) / C\$53.75 (FOB origin)

Maintenance

W-Clean with water-based cleanser.

Testing

Flammability: ASTM E84 Adhered

CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 200+ hours



Specifications
Windswept
300245

Knoll Textiles

Environmental

Greenguard Gold Certified
Contains Recycled Content
FR Free
Free of Intentionally Added PFAS

Warranty

10 years.

© 2022 Knoll, Inc.

Complete product information at [knolltextiles.com](https://www.knolltextiles.com)
800.645.3943



001 Snowfall




002 Zephyr



003 Hummingbird




004 Cliffside



005 Surf



006 Thunder



007 Nighthawk