

# Specifications

## Wood Wall As Safari Vest

### 399470

**maharam**

#### Application

Walls

#### Characteristics

Content: 65% Cellulose, 35% Latex

Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' H x 14' 10" W (305cm x 451cm)

Traffic: Moderate Traffic

Customs: Repeatable, Scalable

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment.

#### Price

Installation is sized, priced and produced on a project-specific basis.

#### Maintenance

W-Clean with water-based cleanser.



#### Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

CAN ULC S102 Adhered

ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications  
Wood Wall As Safari Vest  
399470

**Environmental**


Greenguard Gold Certified  
LBC Red List Free  
Contains Bio-Based Content  
FR Free  
Free of Intentionally Added PFAS

**Warranty**

3 years.

© 2010 Phoebe Washburn, Maharam under license

Complete product information at [maharam.com](http://maharam.com)  
800.645.3943



001